# suttontools

ENGINE

Data Sheets Reference Tables

ormulae

0

charts



• Literature • Cutting Lubricant

# **Others** Black Books

# **Black** Book

#### The ultimate reference book

ε

- Pocket sized - grease / tear proof - lay-flat format

GINEERS

100

- Ideal for engineers, trades people, apprentices,
- machine shops, tool rooms, technical colleges




Large Edition

NEV









#### L103V3EN

G Codes

Hardening and

tempering

Geometrical

standards

Tolerances

construction

Weights of metal

Engineering drawing

Keys and keyways

Tapping drill sizes

Equivalent charts

Speeds & feeds

and more...

Formulae

#### Engineers Black Book - 234 Pages of:

- Tables
- Standards
- Illustrations
- Grinding wheels
- Conversion factors
- Tapers
- Lubricants-coolants
- Bolts and nuts
- Spur gear calculations
- Tungsten carbide
- Plastics
- Sharpening information

#### Electrical Black Book - 212 Pages of:

- Electrical safety laws of electricity electrical conductors
- Electrical codes and standards
- Electrical conduit and conduit bending
- Electrical formulae and conversion factors transformers and motors
- Electrical socket-outlets, switches and enclosures
- Led lighting, fibre optics and data cabling and more...

#### L200V1EN

#### Fastener Black Book - 248 Pages of:

Screw thread

- Tolerances
- Fastener strengths

#### **Discount Group: Z0502**

	Description	Edition	Pages	Carton Qty	Bonus	ltem #	List Price
						L100	
W	Engineers Black Book	Зrd	234	40	Labelling Tabs	L100V3EN	\$63.29
5						L1(	)3
ENV)	Engineers Black Book - Large Edition	Зrd	234	20	Labelling Tabs	L103V3EN	\$79.70
						L2(	00
	Fasteners Black Book	1st	248	40	Thread Pitch Gauge	L200V1EN	\$63.29
						L30	00
W)	Electrical Black Book	2nd	212	40	Labelling Tabs	L300V2EN	\$63.29

192

- fundamentals Standards Heat treatment Dimensional Thread classes Grades Galling Materials and coatings Failures and Torque control Platings corrosion Thread terminology Elevated temperature effects

  - and markings

- Hydrogen embrittlement
- Screw thread profiles
- specifications DIN / ISO / ANSI
- Material selection

# suttontools

Venom Endurance+ Cutting Fluid Venom Endurance+ Cutting Fluid is a highly efficient cutting and

lubricating fluid. Formulated to increase tool life and enhance cutting performance in a broad range of metals including carbon steel, aluminium alloys, copper, brass, bronze and stainless steel. Mild clinging action helps fluid adhere to the tool and part when vertical work is required.

#### **Venom Extreme Power Cutting Paste**

Formulated for superior tool life and cutting performance in carbon steel, aluminium alloys, copper, bronze, stainless steel, nickels, titaniums and other super alloys.

Venom Extreme Power Cutting Paste is a high performance low melting point lubricant specifically designed to adhere to the cutting edges, even when using additional coolants.

	Description		Dis	Discount Group Z100	
Size Ref.		Size	ltem #	List Price	
			M800		
0050	Venom Cutting Fluid**	50ml	M800 0050	\$10.24	
0250	Venom Cutting Fluid	250ml	M800 0250	\$17.20	
0300	Venom Cutting Spray*	300g	M800 0300	\$19.93	
0400	Venom Cutting Paste	400g	M800 0400	\$34.20	
4000	Venom Cutting Fluid	4L	M800 4000	\$194.39	
Only availab	le in multiples of 6 **Onl	v available in multiples of 12			

nly available in multiples of 6 Only available in multiples of 12

#### EXTREME POWER **CUTTING PASTE**

#### Features


- Low melting point adheres to cutting edge for greater tool protection
- Not affected by coolant
- Lowest torque required for higher performance
- Reduced friction for extremely high quality surface finish



enom

M800 0400





### ENDURANCE+ **CUTTING FLUID**

#### Features

- Reduces torque and friction
- Extends tool life
- Improves surface finish
- Accurate thread quality
- Environmentally friendly mineral oil base with 10% organic coconut oil. Free from Trichloroethane – low odour.

## ENDURANCE **CUTTING SPRAY**

#### Features

- Comfort nozzle allows an accurate spray flow in hard-to-reach working areas
- Precise spray flow within 1.5m range
- Non-flammable
- Reduces torque and friction
- Extends tool life
- Improves surface finish
- Accurate thread quality
- Environmentally friendly mineral oil base with 10% organic coconut oil. Free from trichloroethane – low odour.
- Suitable for use in non-ventilated areas



M800 0250

M800 4000



